

TEIJIN POLYCARBONATE SINGAPORE PTE LTD

#01-01, 111 SAKRA AVE, SINGAPORE 627881 SG

LN-2250(##)(f1)

Polycarbonate (PC), "Panlite", furnished as pellets, powder

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI		RTI
					Elec	Imp	Str
ALL	0.43	V-2	-	-	80	80	80
	3.0	V-0	3	0	125	115	125
	6.0	V-0	3	0	125	115	125

Comparative Tracking Index (CTI): 3

Dielectric Strength (kV/mm): -

High-Voltage Arc Tracking Rate
(HVTR): 3

Dimensional Stability (%): 0

Inclined Plane Tracking (IPT): -

Volume Resistivity (10^x ohm-cm): -

High Volt, Low Current Arc Resis (D495): 6

(##) - May be suffixed with one or two letters except for a single letter U, V or Z or the letters U, V or Z followed by another letter.

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1999-07-29
Last Revised: 2013-04-02

© 2013 UL LLC

**IEC and ISO Test Methods**

Test Name	Test Method	Units	Thickness	
			Tested (mm)	Value
Flammability	IEC 60695-11-10	Class (color)	0.43	V-2 (ALL)
			3.0	V-0 (ALL)
			6.0	V-0 (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m ²	-	-
ISO Izod Impact	ISO 180	kJ/m ²	-	-
ISO Charpy Impact	ISO 179-2	kJ/m ²	-	-

© 2013 UL LLC