

CHI MEI CORPORATION

59-1 SAN CHIA, JEN TE, TAINAN HSIEN 71702 TW

PA-758R

Acrylonitrile Butadiene Styrene (ABS), "Polylac", furnished as sheets

	Min Thk	Flame			RTI	RTI	RTI	IEC	IEC
Color	(mm)	Class	HWI	HAI	Elec	Imp	Str	GWIT	GWFI
ALL	1.5	HB	3	0	60	60	60	-	-
	3.0	HB	3	0	60	60	60	-	-

Comparative Tracking Index (CTI): **0**

IEC Comparative Tracking Index (V): **-**

High-Voltage Arc Tracking Rate (HVTR): **0**

High Volt, Low Current Arc Resis (D495): **5**

IEC Ball Pressure (°C): **-**

Dimensional Stability (%): **-**

Dielectric Strength (kV/mm): **-**

Volume Resistivity (10xohm-cm): **-**

ISO Tensile Strength (MPa): **-**

ISO Flexural Strength (MPa): **-**

ISO Tensile Impact (kJ/m2): **-**

ISO Heat Deflection (°C): **-**

ISO Izod Impact (kJ/m2): **-**

ISO Charpy Impact (kJ/m2): **-**

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.