

**CHI MEI CORPORATION**

59-1 SAN CHIA JEN TE TAINAN HSIEN TAIWAN

Material Designation: **PA-765 (+)**

Product Description: Acrylonitrile Butadiene Styrene (ABS), designated "Polylac" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.5	V-0, 5VB	0	0	80	80	80	-	-
	2.5	V-0, 5VA	2	0	80	80	80	-	-
	3.0	V-0, 5VA	0	0	80	80	80	-	-

**CTI: 1 IEC CTI: - HVTR: 0 D495: 7 IEC Ball Pressure (°C): -**

Dielectric Strength (kV/mm): -  
 ISO Tensile Strength (MPa): -  
 ISO Tensile Impact (kJ/m<sup>2</sup>): -

Volume Resistivity (10<sup>9</sup>ohm-cm): -  
 ISO Flexural Strength (MPa): -  
 ISO Izod Impact (kJ/m<sup>2</sup>): -

Dimensional Stability(%): -  
 ISO Heat Deflection (°C): -  
 ISO Charpy Impact (kJ/m<sup>2</sup>): -

(+) Optional prefix or suffix may be used to denote 0-0.5% acid scavengers.

Report Date: 6/23/1983

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by

ULI.