

**CHI MEI CORPORATION**

59-1 SAN CHIA JEN TE TAINAN HSIEN TAIWAN

Material Designation: **PA-777E**

Product Description: Acrylonitrile Butadiene Styrene/Phenyl Maleimide (ABS/PMI), designated "Polylac" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.5	HB	4	0	50	50	50	-	-
	3.0	HB	4	0	50	50	50	-	-

**CTI: 0**      **IEC CTI: -**      **HVTR: 1**      **D495: 6**      **IEC Ball Pressure (°C): -**

Dielectric Strength (kV/mm): -  
 ISO Tensile Strength (MPa): -  
 ISO Tensile Impact (kJ/m<sup>2</sup>): -

Volume Resistivity (10<sup>9</sup>ohm-cm): -  
 ISO Flexural Strength (MPa): -  
 ISO Izod Impact (kJ/m<sup>2</sup>): -

**Dimensional Stability(%)**: -  
**ISO Heat Deflection (°C)**: -  
**ISO Charpy Impact (kJ/m<sup>2</sup>)**: -

Report Date: 3/10/1993

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by

ULI.