

CHI MEI CORPORATION

59-1 SAN CHIA, JEN TE, TAINAN HSIEN 717 TW

PC-540

Polycarbonate/Acrylonitrile Butadiene Styrene (PC/ABS), "Wonderloy", furnished as pellets

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
ALL	0.75	HB	3	3	60	60	60
	1.5	V-0	3	3	70	70	70
	2.0	V-0, 5VB	3	3	70	70	70
	3.0	V-0, 5VB	3	2	75	75	75

Comparative Tracking Index (CTI): 2

High-Voltage Arc Tracking Rate (HVTR): 3

Dielectric Strength (kV/mm): -

Dimensional Stability (%): -

High Volt, Low Current Arc Resis (D495): 5

Volume Resistivity (10^X ohm-cm): -

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2001-01-12

Last Revised: 2011-05-16

Underwriters Laboratories Inc®

