

CHI MEI CORPORATION

59-1 SAN CHIA JEN TE TAINAN HSIEN 71702 TW

Material Designation: **PN-107(+)**

Product Description: Styrene Acrylonitrile (SAN), designated "Kibisan" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.5	HB	4	0	50	50	50	-	-
	3.0	HB	3	0	50	50	50	-	-
CTI: 1	IEC CTI (V): -	HVTR: 0	D495: 6			IEC Ball Pressure (°C): -			
Dielectric Strength (kV/mm): -		Volume Resistivity (10*ohm-cm): -			Dimensional Stability(%): -				
ISO Tensile Strength (MPa): -		ISO Flexural Strength (MPa): -			ISO Heat Deflection (°C): -				
ISO Tensile Impact (kJ/m²): -		ISO Izod Impact (kJ/m²): -			ISO Charpy Impact (kJ/m²): -				

(+) Optional prefix or suffix may be used to denote 0-0.5% acid scavengers.

Report Date: 5/12/1983

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.